

| | |
|--------------------------------------|--|
| Engine | 4 cycle OHV V-Twin gasoline engine, electronic ignition, full pressure lubrication and oil filter. 3 year engine warranty |
| Model | Kohler Command Pro |
| Horsepower | 23 |
| Displacement | 747cc |
| Cooling | Air Cooled |
| Starting | Electric |
| Brakes | Hydraulic |
| Steering | One piece ergonomic handlebar steering control with mounted brake lever. For safety and ease handling, the ARGO steering transmission provides continuous torque to all axles. |
| Controls | Right-hand twist grip throttle. Light switch and ignition switch. |
| Clutch | Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission. |
| Transmission | Planetary differential transmission with High and Low range; Forward, Neutral, Reverse. |
| Drive System | Roller chains drive machined sprockets that are spline-fit onto 1 1/4" diameter axles. Bearings are greasable. |
| Frame | Formed steel channel construction, welded for high strength and durability. Polyester powder-coated for lasting protection |
| Body | Vacuum formed High Molecular Weight Polyethylene. |
| Full Skid Plate | Optional |
| Load Capacity - On Land | 1000 lb. / 454 kg |
| Load Capacity - On Water | 900 lb. / 408 kg |
| Towing Capacity | 1400 lb. / 635 kg |
| Seating Capacity - On Land | 6 persons |
| Seating Capacity - On Water | 4 persons |
| Fuel Capacity | 7.1 US Gallons (27 litres) See through polyethylene fuel tank. 8 hours of operation based on load and operating conditions. |
| Speed (on land) | 19 mph / 30 km per hour |
| Speed (on water) | 3 mph / 5 km per hour |
| Shipping Weight | 1090 lb. / 476 kg |
| Axle Bearing Extensions Front | Standard |
| Axle Bearing Extensions Rear | Optional |
| LCD Digital Gauge Cluster | Speedometer, Odometer, Voltmeter, Hourmeter, Tachometer, Low Oil Pressure and Parking Brake Reminder Lights, Check Engine Light |
| Tires | ARGO AT189 24 x 10.00-8NHS |
| Ground Pressure | 1.7 psi (13.5 kPa) using tires, 0.67 psi (4.6 kPa) using tracks |
| Ground Clearance Tires | 9" (230 mm) |
| Ground Clearance Tracks | 10" (255 mm) |
| Operating Conditions | All weather, all terrain, -40C to +40C |

